

SPECIFICATIONS

Power Requirements	6.0V DC (5.0 to 9.0VDC allowable)
Ground Type	Negative ground type
Max. Power Consumption	1.2W (6.0V)
Output Image	Normal image, CVBS (NTSC video signal) Image output for 16:9 wide-screen
Image Output Impedance	75Ω (1vp-p)
Image Sensor	1/4 inch CMOS image sensor, aspect ratio 4:3
Effective Number of Pixels	1280 (horizontal)×960 (vertical) approximately 1.2 Mega pixels
Lens Section	Focal length f=1.27mm, brightness F=1.8
Angle of Field	Approximately 180° horizontally, approximately 70° vertically
Automatic image Adjusting Function	Automatic exposure adjustment, automatic white balance adjustment
Synchronization System	Internal synchronization
Luminance S/N	8.41 Lx
Resolution (horizontal)	330 TV lines or more (center area)
Illumination Range	Approximately 1.5Lx to 100kLx
Operating Temperature Range	Camera section: -22 to +158F (-30 to +70°C)
Water Resistance	IP68
External dimensions (W×H×D)	Camera section: 23.6×23.6×26.1mm (excluding projection on the rear)
Weight	Camera section: 41g (including cable but not including bracket and screw)

NOTE:

For product improvement, specifications and design are subject to change without notice.